

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
4 August 2005 (04.08.2005)

PCT

(10) International Publication Number  
**WO 2005/071249 A1**

(51) International Patent Classification<sup>7</sup>: F02M 25/03,  
F02B 47/02

(74) Agent: DR. LUDWIG BRANN PATENTBYRÅ AB;  
Box 17192, S-104 62 Stockholm (SE).

(21) International Application Number:  
PCT/SE2005/000065

(22) International Filing Date: 21 January 2005 (21.01.2005)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0400129-3 22 January 2004 (22.01.2004) SE

(71) Applicant (for all designated States except US):  
CARGINE ENGINEERING AB [SE/SE]; Kom-  
panigatan 10, 1tr, S-254 38 Helsingborg (SE).

(72) Inventor; and


(75) Inventor/Applicant (for US only): HEDMAN, Mats  
[SE/SE]; Båvensvik, S-640 34 Sparreholm (SE).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: A METHOD AND A SYSTEM FOR CONTROL OF A DEVICE FOR COMPRESSION



(57) Abstract: A method of compressing a medium in the combustion chamber of a combustion engine, by which method a liquid, in the state of a spray, is introduced into the compression chamber during a compression stroke, the liquid is pressurized and heated before it is introduced into the compression chamber to such a degree that at least a part of the droplets of the spray explode spontaneously upon entrance in the compression chamber, the liquid being pressurized to such an extent that, at the moment of introduction, it has a steam pressure that is above the pressure that, at the moment of introduction, exists in the compression chamber, and the liquid being heated to such an extent that, at the moment of introduction, it has a temperature that exceeds the boiling point of the liquid for the temperature and the pressure that, at the moment of introduction, exists in the compression chamber, and the heat being water. The liquid is heated to such an extent that, at the moment of introduction, it has a temperature that is below the temperature of the medium at the moment of introduction of the liquid.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*